

# SELF-CONTAINED DUMP TRAILER



Item	Specification
Structure	12" 19lb. Beams, Carbon Steel, Fully Welded
Hydraulic System	12 gpm @ 2000 psi or 2 gpm @ 3200 psi
Control System	3 - Way, 3 - Control Valve Manifold with Optional Remote Control
Power Unit	15 hp, Single Cylinder Diesel or Gas Motor with Safety Switches or 2 hp Electric Unit
Axles	2 - 10,000 lbs Heavy Duty Dully with Disc Brakes
Suspension	Tandem Heavy Duty 10,000 to 15,000 lbs
Brake System	Electric over Hydraulic, Self Charging with Safety Brake Away
Lift System	2 - 4" Hydraulic Cylinders, Double Acting or Single Point Scissors
Wheels	8 - D/W 16 x 6 x 865 3,000 lbs (8 studs)
Safety Equipment	DOT reflectors, DOT bumper, Security Trailer Chains, Brake-Away Brake System
Options	Goose Neck, Pintle or Ball Hitch, Hydraulic operated Door, Raising and Latching



842 BUSCHONG  
HOUSTON, TX 77039

RECYCLING EQUIPMENT  
DESIGN & FABRICATION

MORE INFORMATION  
[WWW.DOMATEX.NET](http://WWW.DOMATEX.NET)

281.219.1800