

THE TOUGHEST GOOSENECK ROLL-OFF TRAILER IN THE INDUSTRY

- Available with Inverted 5th Wheel and Pintle Hook
- Extra Heavy Duty Gooseneck



Item	GN-20 Specification	GN-30	GN-40
Structure	Carbon Steel, Fully Welded		
Dimensions	33.8 ft L 7.9 ft W 6.33 ft H		
Container Roller Supports	5 - Solid Steel Roller Supports with Internal Brass Bushing, Driven by 2" Solid Steel Pinion Extending the Width of Trailer		
Hydraulic System	12 gpm @ 2000 psi		
Control System	3 - Way, 3 - Control Valve Manifold		
Power Unit	15 hp. Single Cylinder Diesel Motor with Safety Switches	15 hp Single Cylinder	20 hp Double Cylinder
Axles	2 - 10,000 lbs Heavy Duty Dully with Disc Brakes	2-12,000 lbs.	2-15,000 lbs.
Suspension	Tandem Heavy Duty 15,000 lbs.	26,000 lbs.	32,000 lbs.
Brake System	Electric over Hydraulic, Self Charging with Safety Brake Away		
Lift System	2 - 4" Bore Hydraulic Cylinders, Double Acting	2 - 5"	2 - 5"
Pull System	12,000 lbs Line Pull, Direct Planetary Hydraulic Winch	12,000 lbs.	20,000 lbs.
Container Locks	Hydraulic Actuated Heavy Duty Security Lock Downs		
Wheels	8 - D/W 16 x 6 x 865 - 3,000 lbs (8 studs)	16 - 8 studs	17.5 - 10 studs
Safety Equipment	DOT reflectors, DOT bumper, Security Trailer Chains, Brake-Away Brake System, Container Hydraulic Locks Bullnose Rollers Security Locks		
Approx. trailer weight	7,100 lbs.	7,500 lbs.	7,600 lbs.
Load Capacities	20,000 lbs.	26,000 lbs.	32,000 lbs.

* Trailer is painted black unless otherwise specified



842 BUSCHONG
HOUSTON, TX 77039

RECYCLING EQUIPMENT
DESIGN & FABRICATION

MORE INFORMATION
WWW.DOMATEX.NET

281.219.1800
SPEAK WITH UV OR DANNY